

TeleHawk3

Top Specification Telephone Based Door Entry System



Feature loaded, Top-of-the-Range 'Wire-less' Door Entry System (in SS rated stainless steel housing) with, Trades, Porter/Concierge and PAC options in addition to PIN and Remote Admission capability

TeleHawk3 is the flagship of our **TeleHawk** range. It combines in a single unit all the user friendly, security features expected from a comprehensive Access Control system. The electronics module used is a high performance version of the same tried and tested unit used in the **TeleHawk2** but with more than 33 times the capacity and an LCD display it is in a class of its own. **TeleHawk3** is aimed at architects, developers and installers involved in large new builds, renovation and restoration projects looking for an aesthetically sympathetic, unobtrusive, secure, all-in-one Access Control solution.

TeleHawk3 offers the same non-hard-wired, intercom-unit-free advantages to the installer as the other models in the **TeleHawk** range. Its maximum capacity is 1000 call points. Admission may be gained simply by entering a valid PIN number. Callers/visitors can enter a valid flat/apartment/unit number. **TeleHawk3** then calls the telephone number associated with the flat, apartment or unit. If this number is busy or there is no reply, it can automatically try a second number, which could be a mobile phone.

Typical Applications:
Apartment blocks; Office blocks; Gated housing; Business Parks; Marinas; Emergency call points; Car Parks; Gates and Barriers.

SIMPLE TO USE

All instructions needed to operate the system are displayed in the display window of the panel. All the visitor needs to do is to enter the apartment /house number on the keypad and press the Call button. **TeleHawk3** dials the telephone number of the resident, who after talking to the caller, can open the entrance door/gate by entering a code on the telephone keypad. The resident recognizes that the call is from the panel from the audible panel signal transmitted to the telephone.

SIMPLE TO INSTALL

As the system does not require cabling to each apartment, installation is quick and easy. In most cases completed within one working day.

SIMPLE TO PROGRAM

Programmable by the installer by either using the **TeleHawk3** keypad or by dialing into the system via the dedicated telephone line. Alternatively programming may be contracted to the Veermount programming service.

LINE CONNECTIVITY

TeleHawk3 can be connected to a standard two wire telephone line, or to a PBX extension provided that the extension meets the TBR21 specification. **TeleHawk3** can also be configured with a GSM dialer to provide full connectivity to the GSM network.

COST EFFECTIVE

The combined cost of equipment and installation is only a small fraction of the combined cost of hard wired systems. Larger the building, greater the saving.

APPLICATIONS

APARTMENT BLOCKS - **TeleHawk3** can be installed for any apartment block with up to 1,000 call points. If there is a Porter on duty all calls from the entrance panel can be addressed to the Porter who then controls access to the building.

OFFICE BLOCKS AND SERVICED OFFICES - In an office block occupied by a number of different companies each of the tenants will have control of their callers from their office quickly and efficiently.

BUSINESS PARKS - Just like with serviced offices **TeleHawk3** empowers the occupants of each unit to deal with their visitors when they arrive at the main gate. Employees gain access by entering their PIN number, or using their PAC card if **TeleHawk3** is equipped with a PAC reader.

DESIGN AND MANUFACTURE

All **TeleHawk** systems are designed and manufactured in the UK. They incorporate the latest tried and tested technology and are built with reliability in mind. They are supplied with the manufacturer's warranty and backed up by skilled technical support.

FEATURES

Up to 1,000 call points; Panel signal to the telephone to indicate that the call is from the entry panel; Display window with full instructions; PIN number for each call point; Two telephone numbers for each call point; Admission by entering a valid PIN number; Weather proof stainless keypad; secure pin and trades button feature; Available in both flush mounted and surface mounted construction.

OPTIONAL FEATURES

Mono or Colour video camera; Trade button; Concierge button; Backlit keypad; PAC reader connectivity; Instructions in Braille characters; UPS power supply; Can be configured with a GSM dialer; Connection via mini PBX allows more than one entry point to share the same telephone line; Can be connected to House TV service to display caller on a specified channel on the residents TV; (requires camera), PC based software to store and download database.

POWER SUPPLY

Comes with a power supply that also supplies a 12V dc supply for the strike or magnetic lock.

DIMENSIONS

Flush mounted system	H 340mm	W 185mm	D 58mm
Surface mounted system	H .325mm	W 168mm	D 80mm at top 58mm at bottom
Flush mounted system with Pac	H 426mm	W 185mm	D 58mm